2K 2

3.907.403)76N/

United States Pa

OR

Maeda

3,907,403

ept. 23, 1975

[54]	FIBRE-OPTICS FACEPLATE OBSERVABL WITH HIGH-INTENSITY AMBIENT			
	ILLUMINA	JMINATION		
[75]	Inventor:	Haruo Maeda, Kadoma, Japan		

[73] Assignee: Matsushita Electric Industrial Co.,

Ltd., Kadoma, Japan

[22] Filed: June 18, 1974

[21] Appl. No.: 480,364

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 286,263, Sept. 5, 1972, abandoned, which is a continuation of Ser. No. 56,894, July 21, 1970, abandoned.

[30]	Foreign A	pplication Priority Data
	July 28, 1969	Japan 44-6068
[52]	U.S. Cl.	350/96 B: 350/276 R: 313/37

[58] Field of Search..... 350/96 B, 276 R, 164, 165, 350/188; 313/372, 475

[56]	References Cited			
	UNITED	STATES PATENTS		
2,364,369	12/1944	Jelley et al	350/164	X


2,612,612	9/1952	Szegho et al 350/276 R X
3,253,500	5/1966	Hicks 350/96 B

Primary Examiner—David H. Rubin Attorney, Agent, or Firm—Depaoli & O'Brien

[57] ABSTRACT

A fibre-optics faceplate for displaying an optical image of high image contrast that is suitable for visual observation under high-intensity ambient illumination. The faceplate is a bundle of side-by-side optical fibres, each having a core with a low numerical aperture of below about 0.4, cladding therearound having an index of refraction less than that of the core, and a light-absorbent glass layer around the cladding. The outer surface of the bundle is roughened and has a coating thereon with an index of refraction less than that of the cores. The inner surface has a fluorescent material thereon for emitting optical signals by application thereto of electrical signals.

3 Claims, 4 Drawing Figures



47